




**101406RGBW**

# RING MAXI DMX RGBW

Designed by  
NAVA + AROSIO

Floodlight for outdoor installation on a façade/wall, with 355° swivel base and allowing horizontal adjustment of +90° / -40°. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium base and head, tempered safety glass, moulded silicone gaskets and o-rings, with screws in stainless steel. Swivel joint with graduated scale and mechanical aiming lock. Built-in LED driver, DMX driver integrated; with 6 x CREE "XML" RGBW LED. IP66 rating.



| light source   | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|----------------|--------------------|-------------------|------------------------|
| <b>RGBW</b>    |                    |                   |                        |
| high-power led | 12°                | 1.000             | 35.71                  |
| high-power led | 25°                | 992               | 35.43                  |
| high-power led | 35°                | 981               | 35.04                  |

**Finish color options:**

- Textured Grey  
RAL 9006
- Anthracite Grey  
RAL 7016
- Matt Black  
(on request)

**DMX ACCESSORIES      CONTROLLERS, SPLITTERS, ETC...**

To be defined together with puk technical department, according to project specifications and after providing installation details.

**Technical features**



**Available on request**



**Technical data**

|              |  |
|--------------|--|
| Wattage      | 28 WATT  |
| IP Rating    | IP66   |
| IK Rating    | IK10   |
| Material     | High corrosion resistance die-cast copper-free aluminum body |
| Coating      | Polyester powder coating with phosphochromating pre-finish   |
| Light source | 6 x CREE "XML" COLOR RGBW LED                                |
| Screws       | Stainless steel  |
| DMX          | DMX interface integrated                                     |
| Transformer  | Electrical power supply 220/240V 50/60Hz built-in            |
| Gasket       | Silicone rubber  |
| Glass        | Tempered   |
| Power cable  | 1 mt. power cable included                                   |
| DMX cable    | DMX in & DMX out cables included                             |
| Gross weight | 4,00 Kg  |

|   |   |
|---|---|
| <p>AC044<br/>SPIKE</p>                 | <p>AC050<br/>HONEYCOMB<br/>LOUVER</p>            |
| <p>AC047<br/>ANTI-GLARE<br/>VISOR</p>  | <p>AC038<br/>TREE STRAP<br/>FOR RING SERIES</p>  |

**AC088 - TREE-BRANCH BRACKET**

Special bracket for Ring Maxi pole mounting, suitable to be used with poles diam. min 76 mm and diam. max 120 mm. Can be positioned on various staggered levels or on a single level, with the same pole. Made in phospho-chromatised and polyester powder coated dia-cast copper-free aluminum material, mouled silicone gaskets and screws in stainless steel.

