


101702

FLAMINGO MINI

Designed by NAVA + AROSIO

Diam. 56 mm micro-projector for external use, ideal to light bushes, flowerbed and gardens in general. Body made in turned and anodized aluminum. In horizontal axis it can be oriented up to 30° down and up to 90° up. Remote 24V DC driver needed, with 1 x CREE "XHP35" LED. IP66 rating.





light source	light beam options		lumen output (l	lumin. efficacy lm) (lm/w)			
3000°K warm-white							
high-power led		4°	510	85.00			
high-power led		10°	489	81.50			
high-power led	V	28°	474	79.00			
4000°K neutral-white							
high-power led		4°	520	86.67			
high-power led		10°	499	83.17			
high-power led	V	28°	484	80.67			
2700°K CCT available on request							

Finish color options:



Matt Black

Technical features









Technical data

Wattage	6 WATT	
IP Rating	IP66	
IK Rating	IK08	
Material	Turned and hard anodized aluminum	
Light source	1 x CREE "XHP35" LED	
Screws	Stainless steel	
Remote driver	Constant voltage 24V DC	
Gasket	Silicone rubber	
Glass	Tempered	
Power cable	1,5 mt. power cable included	
Gross weight	1,80 Kg	



OPTIONAL

AC044 SPIKE



AC067 HONEYCOMB LOUVER



AC038 TREE STRAP



remote driver selection								
brand	manufacturer code	type	watt	IP rate	numbers of fixtures			
Meanwell	LPV-20-24	constant voltage 24V DC	20W	IP67	min 1 - max 3			
Meanwell	LPV-35-24	constant voltage 24V DC	35W	IP67	min 1 - max 5			
Meanwell	LPV-60-24	constant voltage 24V DC	60W	IP67	min 1 - max 9			



AC068 PIPE L 300 mm

Extension pipe length 300 mm made in anodized aluminum.

PIPE L 600 mm

Extension pipe length 600 mm made in anodized aluminum.

AC070 PIPE L 900 mm

Extension pipe length 900 mm made in anodized aluminum.

