





108002

LASER MINI

Skyscraper projector for outdoor installation to wall wash a building façade. Anodized extruded aluminium body, phospho-chromatised and polyester powder coated die-cast copper-free aluminium closing caps, tempered safety glass, moulded silicone gasket and stainless steel screws. 24V DC remote driver needed, with 3 CREE LED. IP66 rating.



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|--|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led |  5° | 600 | 60.00 |

Finish color options:

 Silver

remote driver selection

| brand | manufacturer code | type | watt | IP rate | numbers of fixtures |
|----------|-------------------|-------------------------|------|---------|---------------------|
| Meanwell | LPV-20-24 | constant voltage 24V DC | 20W | IP67 | min1 - max2 |
| Meanwell | LPV-35-24 | constant voltage 24V DC | 35W | IP67 | min1 - max3 |
| Meanwell | LPV-60-24 | constant voltage 24V DC | 60W | IP67 | min1 - max5 |

Technical features



Technical data

| | |
|--------------|---|
| Wattage | 10 WATT |
| IP Rating | IP66 |
| IK Rating | IK07 |
| Material | High corrosion resistance anodized extruded aluminum body, die-cast copper-free aluminum closing caps |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | NR. 3 x 2W CREE LED |
| Screws | Stainless steel |
| Transformer | 24V DC |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Power cable | 0,5 mt. neoprene power cable included |
| Gross weight | 1,10 Kg |

