




109002

BOOK MAXI

Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 20 CREE XP-G3 LED. IP65 rating.



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--|--------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led | 10° | 2.880 | 96.00 |
| high-power led | 30° | 2.736 | 91.20 |
| high-power led | 45° | 2.600 | 86.67 |
| 4000°K neutral-white | | | |
| high-power led | 10° | 3.000 | 100.00 |
| high-power led | 30° | 2.850 | 95.00 |
| high-power led | 45° | 2.708 | 90.26 |
| 2700°K CCT available on request | | | |

Finish color options:

- Textured Grey
RAL 9006
- Anthracite Grey
RAL 7016
- Matt Black
(on request)

Technical features




Available on request




Technical data

| | |
|--------------|--|
| Wattage | 30 WATT |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Material | High corrosion resistance die-cast copper-free aluminum body |
| Coating | Polyester powder coating with phosphocromating pre-finish |
| Light source | NR. 20 CREE "XP-G3" LED |
| Screws | Stainless steel |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Cable gland | Double nickel-plated brass cable gland PG9 |
| Power cable | 1 mt. neoprene power cable included |
| Gross weight | 2,80 Kg |

SHORT FIXING BRACKET



MEDIUM FIXING BRACKET



BOTH included In the standard package

