

201065

HYDROFLOOR MICRO STEEL 01

Round ground-recessed drive-over luminaire for outdoor installation, top cover with one way 1x90° light emission. Body and top cover completely realized in stainless steel AISI 304, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V50-60Hz, with 1 CREE XP-E2 LED. IP67 rating.



Tec	hnica	al fea	tures



Tec	hni	ical	data

Wattage	3 WATT		
IP Rating	IP67		
IK Rating	IK10		
Material	Stainless steel AISI 304		
Light source	NR.1 CREE "XP-E2" LED		
Screws	Stainless steel		
Transformer	Electronic power supply 220/240V 50/60Hz built-in		
Static weight	Max 2000 Kg		
resistance	1 dx 2000 rtg		
-	Silicone rubber		
resistance			
resistance Gasket	Silicone rubber		
resistance Gasket Glass	Silicone rubber Tempered		
resistance Gasket Glass Cable gland	Silicone rubber Tempered M12 1 mt. neoprene power cable		
resistance Gasket Glass Cable gland Power cable	Silicone rubber Tempered M12 1 mt. neoprene power cable included		

light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led		1 x 90°	150	50,00
4000°K neutral-white				
high-power led		1 x 90°	158	52,66

Finish color options:

Stainless Steel

