

Technical features











Available on request


DALI


201078

HYDROFLOOR MINI 01

Round ground-recessed luminaire diam. 138 mm for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and top cover with one window (single light emission 1 x 90°), polycarbonate diffuser, moulded silicone gasket.

Built-in LED driver 220-240V 50-60Hz, with 1 CREE XHP-35 LED. IP67 rating.





light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	1 x 90°	220	24,45
4000°K neutral-white			
high-power led	1 x 90°	240	26,67
2700°K CCT available on	request		

Finish color options:







Technical data

Wattage		9 WATT
IP Rating		IP67
IK Rating		IK10
Material		High corrosion resistance die-cast copper-free aluminum
Trim		High corrosion resistance die-cast copper-free aluminum
Coating		Polyester powder coating with phosphocromating pre-finish
Light sou	ırce	NR. 1 CREE XHP35 LED
Screws		Stainless steel
Transforn	ner	Electrical power supply 220/240V 50/60Hz built-in
Gasket		Silicone rubber
Diffuser		Polycarbonate
Cable gla	and	M20
Power ca	ble	1 mt. neoprene power cable included
Gross we	ight	2,00 Kg



