


206002

HYDROFLOOR MEDIUM INVISA

ALL BLACK APPEARANCE.

Round compact ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket, non-visible stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 9 CREE XP-G2 LED + special optics with "invisa-light" technology. IP67 rating.






light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	15°	1.296	86.40
high-power led	35°	1.231	82.07
high-power led	55°	1.170	78.00
4000°K neutral-white			_
high-power led	15°	1.350	90.00
high-power led	35°	1282	85.47
high-power led	55°	1.218	81.20

Finish color options:





Technical features













Available on request


+/-15°





Technical data

reelilileal data			
Wattage	15 WATT		
IP Rating	IP67		
IK Rating	IK10		
Material	High corrosion resistance die-cast copper-free aluminum body		
Coating	Polyester powder coating with phosphocromating pre-finish		
Trim	Stainless steel AISI 304		
Light source	NR. 9 x 1.5W CREE "XP-G2" LED		
Transformer	Electronic power supply 220/240V 50/60Hz built-in		
Screws	Stainless steel		
Optics	Special optics with "invisa-light" technology		
Gasket	Silicone rubber		
Glass	Tempered		
Cable gland	Double M20		
Static weight resistance	Max 5000 Kg		
Power cable	1 mt. neoprene power cable included		
Gross weight	3,00 Kg		
Included	Polypropilene housing for recess included		



Stainless steel finish trim available on request



Sliding hooking system for recessing box

