

## 207005

# **ERRA MINI WALL-WASHER**

Diameter 140mm ground-recessed luminaire for outdoor installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, , with 16 x mid-power SAMSUNG 2835 LED. IP67 rating.

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
mid-power led	WALL-WASHER	450	75.00
3000°K warm-white	,		
mid-power led	WALL-WASHER	470	78.34
4000°K neutral-white	•		
mid-power led	WALL-WASHER	490	81.67

## Finish color options:



Stainless Steel

#### **Technical features**












#### **Available on request**







### **Technical data**

Wattage	6 WATT	
IP Rating	IP67	
IK Rating	IK10	
Material	high corrosion resistance die-cast copper-free aluminum	
Trim	Stainless steel AISI 316L	
Coating	polyester powder coating with phosphocromating pre-finish	
Light Source	Nr. 16 x mid-power SAMSUNG 2835 LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	M20	
Power cable	1 mt. neoprene power cable included	
Gross weight	2,70 Kg	

