

207006

TERRA MINI BLADE

Diameter 140mm ground-recessed luminaire for outdoor installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 1 CREE "XHP35" LED. IP67 rating.

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
high-power led	8° x 170°	560	70.00
3000°K neutral-white			
high-power led	8° x 170°	582	72.75
4000°K neutral-white	<u> </u>		
high-power led	8° x 170°	600	75.00

Finish color options:



Stainless Steel

Technical features












Available on request







Technical data

Wattage	8 WATT	
IP Rating	IP67	
IK Rating	IK10	
Material	high corrosion resistance die-cast copper-free aluminum	
Trim	Stainless steel AISI 316L	
Coating	polyester powder coating with phosphocromating pre-finish	
Light Source	Nr. 1 CREE XHP35 LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built in	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	M20	
Power cable	1 mt. neoprene power cable included	
Gross weight	2,70 Kg	

