




208004

FACE-UP MEDIUM HP

Uplight for outdoor installation on a ground/floor surface. Phosphochromatised and polyester powder coated die-cast copper-free aluminium, tempered safety glass and stainless steel screws. Remote constant current max 700mA needed, with 6 CREE XP-G3 LED. IP67 rating



350 mA - LED POWER 6W

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
high-power led	8°	600	100.00
high-power led	20°	574	95.80
high-power led	40°	556	92.80
3000°K warm-white			
high-power led	8°	612	102.00
high-power led	20°	586	97.80
high-power led	40°	568	94.80
4000°K neutral-white			
high-power led	8°	624	104.00
high-power led	20°	600	99.80
high-power led	40°	580	96.80

Finish color options:

- Textured Grey RAL 9006
- Anthracite Grey RAL 7016
- Matt Black (on request)

Technical features












Technical data










Wattage	MAX 12 WATT
IP Rating	IP67
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminium
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	6 x CREE XP-G3 LED
Screws	Stainless steel
Remote driver	Constant current max 700mA
Glass	Tempered
Power cable	1 mt. power cable included
Gross weight	2,00 Kg



500 mA - LED POWER 9W

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
high-power led	 8°	756	83.75
high-power led	 20°	720	80.25
high-power led	 40°	700	77.75
3000°K warm-white			
high-power led	 8°	774	86.25
high-power led	 20°	746	82.75
high-power led	 40°	720	80.25
4000°K neutral-white			
high-power led	 8°	792	87.88
high-power led	 20°	760	84.50
high-power led	 40°	738	82.00

700 mA - LED POWER 12W


light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
high-power led	 8°	1.076	89.70
high-power led	 20°	1.024	85.33
high-power led	 40°	1.002	83.60
3000°K warm-white			
high-power led	 8°	1.092	90.69
high-power led	 20°	1.044	87.20
high-power led	 40°	1.014	84.60
4000°K neutral-white			
high-power led	 8°	1.116	93.00
high-power led	 20°	1.068	89.00
high-power led	 40°	1.136	86.30

remote driver selection

brand	manufacturer code	type	watt	IP rate	numbers of fixtures
ALVIT Italy	AL1435S-IP	constant current 350mA	14W	IP67	min 1 - max 2
ALVIT Italy	AL1450S-IP	constant current 500mA	14W	IP67	1
ALVIT Italy	AL1470S-IP	constant current 700mA	14W	IP67	1
TCI Italy	152014/350	constant current 350mA	17W	IP68	min 1 - max 2
TCI Italy	152014/500	constant current 500mA	24W	IP68	min 1 - max 2
TCI Italy	152014/700	constant current 700mA	30W	IP68	min 1 - max 2

OPTIONAL

AC121
HONEYCOMB
LOUVER



AC123
SPIKE

