




306003-04

# HYDROFLEX TOP UNDERWATER

1.000 mm / 4.000 mm length, 16mm x 16mm section, opal encapsulated flexible LED strip for linear lighting (straight or bended), underwater installation version; surface mounted version through installation accessories to be ordered separately. LED circuit completely encapsulated with UV and high-temperatures resistant Polyurethane sheath, with white (outside) and milky finish (over light emission), dot free and homogeneous light emission surface. Double power cable with male/female connectors included, suitable for in-line installation. Remote driver 24V DC needed. With nr. 140 low-power SMD3014 Lumileds LED. IP68 rating.




## Technical features




## Technical data

IP Rating	IP68 - 1 Meter DEPTH
Material	High performances Polyurethane, UV resistant, saltwater resistant
	No yellowish after years
	Dot-free and homogeneous light emission
Light source	SMD3014 Lumileds LED
Transformer	24V DC remote driver needed
	Supplied with Male/Female connectors for in-line installation





<b>306003</b>	<b>HYDROFLEX TOP 1000 UNDERWATER</b>		
<b>light source</b>	<b>light beam options</b>	<b>lumen output (lm)</b>	<b>lumin. efficacy (lm/w)</b>
<b>3000°K warm-white</b>			
low power led	 diffused	750	75.00


**Finish color options:**

Milky

<b>Technical data</b>	
Wattage	10 WATT
IP Rating	IP68

<b>remote driver selection</b>					
<b>brand</b>	<b>manufacturer code</b>	<b>type</b>	<b>watt</b>	<b>IP rate</b>	<b>numbers of fixtures</b>
Meanwell	LPV-20-24	constant voltage 24V DC	20W	IP67	1
Meanwell	LPV-35-24	constant voltage 24V DC	35W	IP67	min 1 - max 2
Meanwell	LPV-60-24	constant voltage 24V DC	60W	IP67	min 1 - max 5
Meanwell	LPV-100-24	constant voltage 24V DC	100W	IP67	min 1 - max 9



<b>306004</b>	<b>HYDROFLEX TOP 4000 UNDERWATER</b>		
<b>light source</b>	<b>light beam options</b>	<b>lumen output (lm)</b>	<b>lumin. efficacy (lm/w)</b>
<b>3000°K warm-white</b>			
low power led	 diffused	3.000	75.00

Milky

<b>Technical data</b>	
Wattage	40 WATT
IP Rating	IP68

<b>remote driver selection</b>					
<b>brand</b>	<b>manufacturer code</b>	<b>type</b>	<b>watt</b>	<b>IP rate</b>	<b>numbers of fixtures</b>
Meanwell	LPV-60-24	constant voltage 24V DC	60W	IP67	1
Meanwell	LPV-100-24	constant voltage 24V DC	100W	IP67	min 1 - max 2

**AC034 MOUNTING CLIP FOR HYDROFLEX TOP**

Mounting clip for Hydroflex Top, realized in Stainless steel, clip to be applied every 40 cm, to secure with screws. Ideal for bended installation on a wall or ceiling.



**AC035 ALUMINUM LINEAR PROFILE FOR HYDROFLEX TOP**

1.000 mm Linear profile for Hydroflex Top, realized in Anodized aluminum.

