

Technical features










401604

SURF MEDIUM SQUARE

Square wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 14 mid-power CREE XH-G LED. IP65 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	floor washer 180°	650	81.25
4000°K neutral-white*			
mid power led	floor washer 180°	683	85.38
2700°K CCT available on	request		

^{*} Available on request

Finish color options:







Technical data

Wattage	8 WATT	
IP Rating	IP65	
IK Rating	IK08	
Material	High corrosion resistance die-cast copper-free aluminum body and frame.	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	NR. 14 x CREE XH-G LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Tempered	
Rubber grommet	M16 Rutaseal® in EPDM	
Gross weight	1,40 Kg	

