


401704

ECLIPSE MINI SQUARE 02

PAOLO VILLA

Square wall surface-mounted luminaire creating a bi-directional (up&down) wall-washer lighting effect on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2x6 mid-power CREE XH-G LED. IP65 rating.





light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	2 x 30°	2 x 350	87,50

^{*} Other light colors available on request: Neutral-white

Finish color options:







Technical features









Technical data

Wattage	8 WATT	
IP Rating	IP65	
IK Rating	IK08	
Material	High corrosion resistance die-cast copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	Nr. 2 x 6 mid-power CREE XH-G LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Rubber grommet	M12 Rutaseal® in EPDM	
Diffuser	Polycarbonate	
Gross weight	1,00 Kg	



