




401705

ECLIPSE MEDIUM ROUND


Designed by
PAOLO VILLA

Round wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.



| light source* | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|---------------|--------------------|-------------------|------------------------|
|---------------|--------------------|-------------------|------------------------|

3000°K warm-white

| | | | |
|---------------|--|-----|-------|
| low power led |  360° | 556 | 46.33 |
|---------------|--|-----|-------|

* Other light colors available on request: Neutral-white

Finish color options:

| | | |
|--|---|--|
|  Textured Grey RAL 9006 |  Anthracite Grey RAL 7016 |  Matt Black (on request) |
|--|---|--|

Technical features



Technical data

| | |
|----------------|--|
| Wattage | 12 WATT |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Material | High corrosion resistance die-cast copper-free aluminum body |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | Low-power CREE LED |
| Screws | Stainless steel |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in |
| Gasket | Silicone rubber |
| Rubber grommet | M16 Rutaseal® in EPDM |
| Diffuser | Polycarbonate |
| Gross weight | 1,50 Kg |

