




402604

TECH EVO MEDIUM 02

Designed by MOMO DESIGN

Up & down wall applique for outdoor installation. Phosphochromatised and polyester powder coated copper-free extruded aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 1 COB CREE "CXB 1512" LED. IP 65 rating.



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|--------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| cob led | 14° | 2 x 1.951 | 130.06 |
| cob led | 35° | 2 x 1.850 | 123.33 |
| cob led | 55° | 2 x 1.800 | 120.00 |
| 4000°K neutral-white | | | |
| cob led | 14° | 2 x 2.240 | 149.33 |
| cob led | 35° | 2 x 2.131 | 142.06 |
| cob led | 55° | 2 x 2.046 | 136.40 |

2700°K CCT available on request

Finish color options:

- Textured Grey RAL 9006
- Anthracite Grey RAL 7016
- Matt Black (on request)

Technical features



Available on request



Technical data

| | |
|--------------|--|
| Wattage | 30 WATT |
| IP Rating | IP65 |
| IK Rating | IK09 |
| Material | High corrosion resistance extruded copper-free aluminum body |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | NR. 2 x 1 COB CREE "CXB 1512" LED |
| Screws | Stainless steel |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in |
| Cable gland | M16 rubber grommet |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Power cable | 1 mt. neoprene power cable included |
| Gross weight | 3,50 Kg |



Optional: Opal Glass Diffuser