

Technical features



Technical data









Available on request

DALI

402801

FRAME MEDIUM ROUND

Designed by NAVA + AROSIO

Round diam. 210mm surface mounted luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, acid-etched tempered glass diffuser white painted internally, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 36 \times mid-power SAMSUNG 2835 LED. IP65 rating.





55 mm

Ø 210 mm

68 mm



light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led		diffused	808	50.50
4000°K neutral-white				
high-power led		diffused	844	52.75
2700°K CCT available on	request			

Finish color options:







Wattage	16 WATT	
IP Rating	IP65	
IK Rating	IK09	
Material	High corrosion resistance extruded copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	36 x mid-power SAMSUNG 2835 LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Acid-etched tempered glass diffuser white painted internally	
Power cable	0,3 mt. power cable included	
Gross weight	3,20 Kg	

