

Technical features









Available on request




402802

FRAME MEDIUM SQUARE

Designed by NAVA + AROSIO

Square 200x200mm surface mounted luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, acid-etched tempered glass diffuser white painted internally, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 36 x mid-power SAMSUNG 2835 LED. IP65 rating.











light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led		diffused	808	50.50
4000°K neutral-white				
high-power led		diffused	844	52.75
2700°K CCT available on	request			

Finish color options:







Technical data

Wattage	16 WATT		
IP Rating	IP65		
IK Rating	IKO9		
Material	High corrosion resistance extruded copper-free aluminum body		
Coating	Polyester powder coating with phosphocromating pre-finish		
Light source	36 x mid-power SAMSUNG 2835 LED		
Screws	Stainless steel		
Transformer	Electronic power supply 220/240V 50/60Hz built-in		
Gasket	Silicone rubber		
Glass	Acid-etched tempered glass diffuser white painted internally		
Power cable	0,3 mt. power cable included		
Gross weight	3,50 Kg		



