




403101

## NANOWALL ROUND COB 01

Wall applique for outdoor installation on a façade/wall, with one side light only. Body in anodized aluminum with phosphochromatised and polyester powder coating, tempered safety glass, moulded silicone gasket and stainless steel screws. With 1 direct 220-240V LUMENS "EDC 38C" COB LED. IP66 rating.



| light source                | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|--------------------|-------------------|------------------------|
| <b>3000°K warm-white</b>    |                    |                   |                        |
| cob led                     | 20°                | 400               | 50.00                  |
| cob led                     | 40°                | 390               | 48.75                  |
| <b>4000°K neutral-white</b> |                    |                   |                        |
| cob led                     | 20°                | 410               | 51.25                  |
| cob led                     | 40°                | 400               | 50.00                  |

**2700°K CCT** available on request

### Finish color options:

Textured Grey RAL 9006

Anthracite Grey RAL 7016


Matt Black (on request)

### Technical features



### Technical data

|              |  |
|--------------|--|
| Wattage      | 8 WATT MAX   |
| IP Rating    | IP66   |
| IK Rating    | IK09   |
| Material     | Hard anodized aluminum                                     |
| Coating      | Polyester powder coating with phosphochromating pre-finish |
| Light Source | 1 x LUMENS "EDC 38C" COB LED                               |
| Screws       | Stainless steel  |
| Transformer  | Electrical power supply 220/240V 50/60Hz built-in          |
| Gasket       | Silicone rubber  |
| Glass        | Tempered   |
| Power cable  | 1 mt. power cable included                                 |
| Gross weight | 1,30 Kg  |



AC064  
HONEYCOMB  
LOUVER