




Technical features



403110

NANOWALL SQUARE XXS 02

Wall applique for outdoor installation on a façade/wall, with up&down light. Body in anodized aluminum with phospho-chromatised and polyester powder coating, tempered safety glass, moulded silicone gasket and stainless steel screws. Constant current 350mA remote driver needed. With 2 x CREE "XP-G2" LED. IP66 rating.




Technical data

Wattage	2x1 WATT
IP Rating	IP66
IK Rating	IK08
Material	Hard anodized aluminum
Coating	polyester powder coating with phosphochromating pre-finish
Light Source	2 x CREE "XP-G2" LED
Screws	Stainless steel
Remote driver	Constant current 350mA
Glass	Tempered
Power cable	0.3 mt. power cable included
Gross weight	0,40 Kg

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
high-power led	8°	2x70	70.00
high-power led	32°	2x60	60.00
high-power led	45°	2x55	55.00
3000°K warm-white			
high-power led	8°	2x75	75.00
high-power led	32°	2x65	65.00
high-power led	45°	2x60	60.00
4000°K neutral-white			
high-power led	8°	2x80	80.00
high-power led	32°	2x70	70.00
high-power led	45°	2x65	65.00

Finish color options:



AC0124
HONEYCOMB
LOUVER

remote driver selection

brand	manufacturer code	type	watt	IP rate	numbers of fixtures
ALVIT Italy	AL1435S-IP	Constant current 350mA	14W	IP67	min 1 - max 4
Meanwell	LPC-20-350	Constant current 350mA	16.8W	IP67	min 2 - max 6