


### Technical features



403116

# NANOWALL SQUARE HP 02

Wall applique for outdoor installation on a façade/wall, with up&down light.  
 Body in anodized aluminum with phospho-chromatised and polyester powder coating, tempered safety glass, moulded silicone gasket and stainless steel screws.  
 Constant current max 700mA remote driver needed. With 2 x CREE "XHP35" LED.  
 IP66 rating.

### Technical data

Wattage	Max 2x10 WATT
IP Rating	IP66
IK Rating	IK09
Material	Hard anodized aluminum
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	2 x CREE XHP35 LED
Screws	Stainless steel
Remote driver	Constant current max 700mA
Gasket	Silicone rubber
Glass	Tempered
Power cable	1 mt. power cable included
Gross weight	1,60 Kg

### 350 mA - LED POWER 2x5W

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>2700°K warm-white</b>			
high-power led	4°	2 x 500	100.00
high-power led	10°	2 x 479	95.80
high-power led	28°	2 x 464	92.80
high-power led	55°	2 x 394	78.88
<b>3000°K warm-white</b>			
high-power led	4°	2 x 510	102.00
high-power led	10°	2 x 489	97.80
high-power led	28°	2 x 474	94.80
high-power led	55°	2 x 403	80.58
<b>4000°K neutral-white</b>			
high-power led	4°	2 x 520	104.00
high-power led	10°	2 x 499	99.80
high-power led	28°	2 x 484	96.80
high-power led	55°	2 x 411	82.28

### Finish color options:



**500 mA - LED POWER 2x8W**

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>2700°K warm-white</b>			
high-power led	4°	2 x 670	83.75
high-power led	10°	2 x 642	80.25
high-power led	28°	2 x 622	77.75
high-power led	55°	2 x 529	66.09
<b>3000°K warm-white</b>			
high-power led	4°	2 x 690	86.25
high-power led	10°	2 x 662	82.75
high-power led	28°	2 x 642	80.25
high-power led	55°	2 x 546	68.21
<b>4000°K neutral-white</b>			
high-power led	4°	2 x 703	87.88
high-power led	10°	2 x 676	84.50
high-power led	28°	2 x 656	82.00
high-power led	55°	2 x 558	69.70

**700 mA - LED POWER 2x10W**

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>2700°K warm-white</b>			
high-power led	4°	2 x 897	89.70
high-power led	10°	2 x 762	76.20
high-power led	28°	2 x 836	83.60
high-power led	55°	2 x 711	71.06
<b>3000°K warm-white</b>			
high-power led	4°	2 x 907	90.69
high-power led	10°	2 x 872	87.20
high-power led	28°	2 x 846	84.60
high-power led	55°	2 x 719	71.91
<b>4000°K neutral-white</b>			
high-power led	4°	2 x 930	93.00
high-power led	10°	2 x 890	89.00
high-power led	28°	2 x 863	86.30
high-power led	55°	2 x 734	73.36

**AC114**

**STANDARD GLARE SHIELD**

Glare shield accessory made in hard anodized black aluminum, providing good balance in between glare control and light output.


**AC115**

**SUPER COMFORT GLARE SHIELD**

Glare shield accessory made in hard anodized black aluminum, for applications requiring very reduced glaring; minimal light loss on the light surface but overall lumen output typically reduced by 50%.

**AC064**

**HYONECOMB LOUVER**



AC064  
HONEYCOMB  
LOUVER