

505001

## NANOSTEP ROUND XXS

Round shape wall-recessed luminaire for outdoor installation. Body and frontal cover in hard anodized aluminum with phospho-chromatised and polyester powder coating, tempered safety glass, moulded silicone gasket. Asymmetrical light distribution. Remote constant current 350mA driver needed, with 1 CREE XP-G2 LED. IP68 rating.

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>2700°K warm-white</b>			
high-power led	15°	65	65.00
high-power led	30°	55	55.00
high-power led	45°	50	50.00
<b>3000°K warm-white</b>			
high-power led	15°	70	70.00
high-power led	30°	60	60.00
high-power led	45°	55	55.00
<b>4000°K neutral-white</b>			
high-power led	15°	80	80.00
high-power led	30°	70	70.00
high-power led	45°	65	65.00


### Finish color options:



### remote driver selection

brand	manufacturer code	type	watt	IP rate	numbers of fixtures
ALVIT Italy	AL1435S-IP	constant current 350mA	14W	IP67	min 1 - max 8
Meanwell	LPC-20-350	constant current 350mA	16.8W	IP67	min 4 - max 12

### Technical features



### Technical data

Wattage	1 WATT
IP Rating	IP68
IK Rating	IK08
Material	Hard anodized aluminium body and trim
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	Nr. 1 CREE XP-G2 LED
Remote driver	Constant current 350 mA
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M12
Power cable	0.3 mt. neoprene power cable included
Gross weight	0,50 Kg

