


## 601801

# **BOULEVARD MINI 180**

600mm height bollard, round shape, for outdoor surface installation, 180° light emission, phospho-chromatised and polyester powder coated extruded copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 220-240V 50-60Hz, with 8 CREE JK3030 mid-power LED. IP65 rating.



Ø 110 mm



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid-power led	• 180°	400	61.53
4000°K neutral-white			
mid-power led	• 180°	410	63.08

### Finish color options:

Textured Grey RAL 9006

436 | puk.it

Anthracite Grey RAL 7016 Matt Black (on request) **Technical features** 



#### Available on request



## Technical data

Wattage	6.5 WATT	
IP Rating	IP65	
IK Rating	IK10	
Material	High corrosion resistance extruded copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	NR. 8 x CREE JK3030 LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Diffuser	Polycarbonate diffuser	
Gross weight	4,00 Kg	