

701313

CIELO MAXI HP DMX RGBW

Diameter 254mm ceiling-recessed luminaire for outdoor installation, phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Light source tilt system +/- 15deg from outside. Built-in LED driver, DMX interface integrated; with 6 x CREE "XML" RGBW LED. IP67 rating.

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
RGBW			
high-power led	12°	1.000	35.71
high-power led	25°	992	35.43
high-power led	35°	981	35.04

Finish color options:



Stainless Steel

ACCESSORIES



AC119 HONEYCOMB LOUVER FOR CIELO MAXI

Technical features














Available on request







HOLE FOR RECESS

Technical data

Wattage	28 WATT	
IP Rating	IP67	
IK Rating	IK10	
Material	high corrosion resistance die-cast copper-free aluminum	
Trim	Stainless steel AISI 316L	
Coating	polyester powder coating with phosphocromating pre-finish	
Light Source	Nr. 6 CREE "XML" RGBW LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built-in	
DMX	DMX interface integrated	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	M20 + PG9	
Power cable	1 mt. neoprene power cable included	
DMX cable	DMX IN cable included	
Gross weight	5,70 Kg	

