

# 701314

Diameter 254mm ceiling-recessed luminaire for outdoor installation, phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 66 x mid-power SAMSUNG 2835 LED. IP67 rating.

#### light source light beam options lumin. efficacy lumen output (lm) (lm/w) 2700°K warm-white WALL-WASHER mid-power led 1800 75.00 3000°K warm-white mid-power led WALL-WASHER 1880 78.33 4000°K neutral-white WALL-WASHER mid-power led 1960 81.67

# Finish color options:



Stainless Steel

#### **Technical features**












# Available on request







HOLE FOR RECESS

### **Technical data**

| Wattage      | 24 WATT  |
|--------------|--|
| IP Rating    | IP67   |
| IK Rating    | IK10   |
| Material     | high corrosion resistance<br>die-cast copper-free aluminum |
| Trim         | Stainless steel AISI 316L                                  |
| Coating      | polyester powder coating with phosphocromating pre-finish  |
| Light Source | Nr. 66 x mid-power SAMSUNG<br>2835 LED                     |
| Screws       | Stainless steel  |
| Transformer  | Electrical power supply 220/240V 50/60Hz built-in          |
| Gasket       | Silicone rubber  |
| Glass        | Tempered   |
| Cable gland  | M20  |
| Power cable  | 1 mt. neoprene power cable included                        |
| Gross weight | 5,70 Kg  |
|              |  |

