





Flexa Dot

Nava + Arosio



PRODUCT WEIGHT 0,80 kg



Code Example

907001.27.DF.07.0

Accessories p. 415

Flexa Dot 800

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist flexible stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 820 mm. Remote constant voltage 24V DC power supply needed. IP66 rating



907001
3W
Transparent Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish: .07 Obsidian Black
Dimming: .0 ON/OFF




907002
3W
Opal Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish: .07 Obsidian Black
Dimming: .0 ON/OFF

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



PRODUCT WEIGHT 1,00 kg



Flexa Dot 1100

Code Example

907003.27.DF.07.0

Accessories p. 415

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist flexible stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 1120 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



907003
3W
Transparent Glass

CCT	Beam Angle	Im	Im/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish: **.07** Obsidian Black
Dimming: **.0** ON/OFF



907004
3W
Opal Glass

CCT	Beam Angle	Im	Im/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish: **.07** Obsidian Black
Dimming: **.0** ON/OFF

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8

ACCESSORIES NOT INCLUDED

Accessories to be ordered separately.



AC146

SPIKE

Stainless steel ground spike.

Compatible for all products of the series.