




# Passoluce



PRODUCT WEIGHT 0,50 kg



Code Example

506001,.27,.FW,.01,.0

## Passoluce Mini Round

Round shape wall-recessed luminaire with floor-washer light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.


**506001**

**3W**

CCT	Beam Angle	Im	Im/w	Finish	Dimming
<b>.27</b> 2700°K	<b>.FW</b> Floor Washer	110	36.60	<b>.01</b>  RAL 9006	<b>.0</b> ON/OFF
<b>.30</b> 3000°K	<b>.FW</b> Floor Washer	120	40.00	<b>.02</b>  RAL 7016	
<b>.40</b> 4000°K	<b>.FW</b> Floor Washer	140	46.60	<b>.03</b>  RAL 9005	

### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



PRODUCT WEIGHT 0,50 kg



Code Example

506002·27·DF·01·0

### Passoluce Mini Round Diffused

Round shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.


**506002**

**3W**

CCT	Beam Angle	lm	lm/w	Finish	Dimming
<b>.27</b> 2700°K	<b>.DF</b> Diffused	120	40.00	<b>.01</b> RAL 9006	<b>.0</b> ON/OFF
<b>.30</b> 3000°K	<b>.DF</b> Diffused	130	43.33	<b>.02</b> RAL 7016	
<b>.40</b> 4000°K	<b>.DF</b> Diffused	150	50.00	<b>.03</b> RAL 9005	

#### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



PRODUCT WEIGHT 0,50 kg



Code Example

506003·27·DF·01·0

### Passoluce Mini Round Grid

Round shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body and protection grid, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.


**506003**

**3W**

CCT	Beam Angle	lm	lm/w	Finish	Dimming
<b>.27</b> 2700°K	<b>.DF</b> Diffused	110	36.60	<b>.01</b> RAL 9006	<b>.0</b> ON/OFF
<b>.30</b> 3000°K	<b>.DF</b> Diffused	120	40.00	<b>.02</b> RAL 7016	
<b>.40</b> 4000°K	<b>.DF</b> Diffused	140	46.60	<b>.03</b> RAL 9005	

#### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



Code Example

506004·.27·.FW·.01·.0



PRODUCT WEIGHT 0,50 kg



### Passoluce Mini Square


Square shape wall-recessed luminaire with floor-wahser light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.

**506004**  
**3W**

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.FW Floor Washer	110	36.60	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.FW Floor Washer	120	40.00	.02  RAL 7016	
.40 4000°K	.FW Floor Washer	140	46.60	.03  RAL 9005	

#### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



Code Example

506005·.27·.DF·.01·.0



PRODUCT WEIGHT 0,50 kg



### Passoluce Mini Square Diffused



Square shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.

**506005**  
**3W**

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.DF Diffused	120	40.00	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	130	43.33	.02  RAL 7016	
.40 4000°K	.DF Diffused	150	50.00	.03  RAL 9005	

#### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



PRODUCT WEIGHT 0,50 kg



Code Example

506006·.27·.DF·.01·.0

### Passoluce Mini Square Grid


Square shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body and protection grid, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.

**506006**  
**3W**

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.DF Diffused	110	36.60	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	120	40.00	.02  RAL 7016	
.40 4000°K	.DF Diffused	140	46.60	.03  RAL 9005	

#### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



PRODUCT WEIGHT 0,80 kg



Code Example

506007·.27·.FW·.01·.0

### Passoluce Mini Linear


Linear shape wall-recessed luminaire with floor-wahser light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.

**506007**  
**7W**

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.FW Floor Washer	238	34.00	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.FW Floor Washer	248	35.43	.02  RAL 7016	
.40 4000°K	.FW Floor Washer	268	38.29	.03  RAL 9005	

#### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 2
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 4



PRODUCT WEIGHT 0,8 kg



Code Example

506008,.27,.DF,.01,.0

### Passoluce Mini Linear Diffused

Linear shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.


**506008**

7W

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.DF Diffused	248	35.43	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	258	36.86	.02  RAL 7016	
.40 4000°K	.DF Diffused	278	39.71	.03  RAL 9005	

#### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 2
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 4



PRODUCT WEIGHT 0,80 kg



Code Example

506009,.27,.DF,.01,.0

### Passoluce Mini Linear Grid

Linear shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.


**506009**

7W

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.DF Diffused	238	34.00	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	248	35.43	.02  RAL 7016	
.40 4000°K	.DF Diffused	268	38.29	.03  RAL 9005	

#### Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 2
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 4



PRODUCT WEIGHT 1,00 kg




Code Example

506010,.27,.FW,.01,.0

### Passoluce Medium Round

Round shape wall-recessed luminaire with floor-washer light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

	CCT	Beam Angle		Im	Im/w	Finish	Dimming
<b>506010</b>	.27 2700°K	.FW Floor Washer		296	37.00	.01  RAL 9006	.0 ON/OFF
<b>8W</b>	.30 3000°K	.FW Floor Washer		306	38.25	.02  RAL 7016	.D DALI
	.40 4000°K	.FW Floor Washer		326	40.75	.03  RAL 9005	



PRODUCT WEIGHT 1,00 kg




Code Example

506011,.27,.DF,.01,.0

### Passoluce Medium Round Diffused

Round shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

	CCT	Beam Angle		Im	Im/w	Finish	Dimming
<b>506011</b>	.27 2700°K	.DF Diffused		306	38.25	.01  RAL 9006	.0 ON/OFF
<b>8W</b>	.30 3000°K	.DF Diffused		316	39.50	.02  RAL 7016	.D DALI
	.40 4000°K	.DF Diffused		336	42.00	.03  RAL 9005	



PRODUCT WEIGHT 1,00 kg



Code Example

**506012**.27.DF.01.0


### Passoluce Medium Round Grid

Round shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body and protection grid, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

**506012**

**8W**

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.DF Diffused	296	37.00	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	306	38.25	.02  RAL 7016	.D DALI
.40 4000°K	.DF Diffused	326	40.75	.03  RAL 9005	



PRODUCT WEIGHT 1,00 kg



Code Example

**506013**.27.FW.01.0



### Passoluce Medium Square

Square shape wall-recessed luminaire with floor-wahser light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

**506013**

**8W**

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.FW Floor Washer	296	37.00	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.FW Floor Washer	306	38.25	.02  RAL 7016	.D DALI
.40 4000°K	.FW Floor Washer	326	40.75	.03  RAL 9005	



PRODUCT WEIGHT 1,00 kg



Code Example



506014 · .27 · .DF · .01 · .0

### Passoluce Medium Square Diffused

Square shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

**506014**  
**8W**

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.DF Diffused	306	38.25	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	316	39.50	.02  RAL 7016	.D DALI
.40 4000°K	.DF Diffused	336	42.00	.03  RAL 9005	



PRODUCT WEIGHT 1,00 kg



Code Example


506015 · .27 · .DF · .01 · .0

### Passoluce Medium Square Grid

Square shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body and protection grid, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

**506015**  
**8W**

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.DF Diffused	296	37.00	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	306	38.25	.02  RAL 7016	.D DALI
.40 4000°K	.DF Diffused	326	40.75	.03  RAL 9005	



PRODUCT WEIGHT 1,60 kg



Code Example

506016,.27,.FW,.01,.0


### Passoluce Medium Linear

Linear shape wall-recessed luminaire with floor-washer light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

**506016**

11W

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.FW Floor Washer	495	45.00	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.FW Floor Washer	505	45.90	.02  RAL 7016	.D DALI
.40 4000°K	.FW Floor Washer	525	47.73	.03  RAL 9005	



PRODUCT WEIGHT 1,60 kg



Code Example

506017,.27,.FW,.01,.0


### Passoluce Medium Linear Diffused

Linear shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

**506017**

11W

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.DF Diffused	505	45.90	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	515	46.82	.02  RAL 7016	.D DALI
.40 4000°K	.DF Diffused	535	48.64	.03  RAL 9005	



PRODUCT WEIGHT 1,60 kg



Code Example

506018,.27,.FW,.01,.0

### Passoluce Medium Linear Grid

Lineat shape wall-recessed luminaire with diffused light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body and protection grid, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in driver 220-240V 50-60Hz. IP66 rating.

**506018**

11W

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.DF Diffused	495	45.00	.01  RAL 9006	.0 ON/OFF
.30 3000°K	.DF Diffused	505	45.90	.02  RAL 7016	.D DALI
.40 4000°K	.DF Diffused	525	47.73	.03  RAL 9005	

Accessories p. 13

