




Rondis

Nava + Arosio



PRODUCT WEIGHT 1,50 kg



Code Example

908001.27.AL.07.0

Accessories p. 421

Rondis Rounded 300

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and light head. All structural parts are phospho-chromatised and polyester powder coated. Total height 325 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.




908001
9W

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.AL 360°	450	50.00	.07 Obsidian Black	.0 ON/OFF
.30 3000°K	.AL 360°	465	51.66	.08 Wild Green	
.40 4000°K	.AL 360°	480	53.33	.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	1
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 2



PRODUCT WEIGHT 1,70 kg



Rondis Rounded 600

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and light head. All structural parts are phospho-chromatised and polyester powder coated. Total height 625 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.

Code Example

908002.27.AL.07.0

Accessories p. 421



908002
9W

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.AL 360°	450	50.00	.07 Obsidian Black	.0 ON/OFF
.30 3000°K	.AL 360°	465	51.66	.08 Wild Green	
.40 4000°K	.AL 360°	480	53.33	.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	1
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 2




Obsidian Black



Wild Green



Dark Brown



PRODUCT WEIGHT 1,90 kg



Code Example

908003.27.AL.07.0

Accessories p. 421

Rondis Rounded 900

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and light head. All structural parts are phospho-chromatised and polyester powder coated. Total height 925 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.




908003
9W

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.AL 360°	450	50.00	.07 Obsidian Black	.0 ON/OFF
.30 3000°K	.AL 360°	465	51.66	.08 Wild Green	
.40 4000°K	.AL 360°	480	53.33	.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	1
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 2





PRODUCT WEIGHT 1,50 kg



Code Example

908004.27.AL.07.0

Accessories p. 421

Rondis Flat 300

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and light head. All structural parts are phospho-chromatised and polyester powder coated. Total height 325 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.




908004

9W

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.AL 360°	450	50.00	.07 Obsidian Black	.0 ON/OFF
.30 3000°K	.AL 360°	465	51.66	.08 Wild Green	
.40 4000°K	.AL 360°	480	53.33	.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	1
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 2



PRODUCT WEIGHT 1,70 kg



Code Example

908005.27.AL.07.0

Accessories p. 421

Rondis Flat 600

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and light head. All structural parts are phospho-chromatised and polyester powder coated. Total height 625 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



908005



9W

CCT	Beam Angle	lm	lm/w	Finish	Dimming
.27 2700°K	.AL 360°	450	50.00	.07 Obsidian Black	.0 ON/OFF
.30 3000°K	.AL 360°	465	51.66	.08 Wild Green	
.40 4000°K	.AL 360°	480	53.33	.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	1
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 2





PRODUCT WEIGHT 1,90 kg



Rondis Flat 900

Code Example

908006.27.AL.07.0

Accessories p. 421

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and light head. All structural parts are phospho-chromatised and polyester powder coated. Total height 925 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



908006

9W

CCT	Beam Angle	Im	Im/w	Finish	Dimming
.27 2700°K	.AL 360°	450	50.00	.07 Obsidian Black	.0 ON/OFF
.30 3000°K	.AL 360°	465	51.66	.08 Wild Green	
.40 4000°K	.AL 360°	480	53.33	.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	1
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 2

INTEGRATED ACCESSORIES

908001.27.AL.07.0

Built-in accessories to be requested when ordering example 908001.27.AL.01.0.CD



.CD

COLORED DISC

Colored PMMA disc designed to be combined with Rondis glass diffuser. It becomes luminescent, adding a distinctive aesthetic accent.

ACCESSORIES NOT INCLUDED

Accessories to be ordered separately.



AC146

SPIKE

Stainless steel ground spike. **Compatible for all products of the series.**