




Vetra Dot

Nava + Arosio



PRODUCT WEIGHT 0,70 kg



Vetra Dot 600

Code Example

904001 .27 .DF .07 .0

Accessories p. 407

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 620 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



904001
3W
Transparent Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	



904002
3W
Opal Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60


Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8




Obsidian Black



Wild Green



Dark Brown



PRODUCT WEIGHT 0,90 kg



Vetra Dot 900

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 920 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.

Code Example

904003.27.DF.07.0

Accessories p. 407



904003
3W
Transparent Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	




904004
3W
Opal Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



PRODUCT WEIGHT 1,10 kg



Code Example

904005, .27, .DF, .07, .0

Accessories p. 407

Vetra Dot 1200

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 1220 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



904005
3W
Transparent Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	



904006
3W
Opal Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8

ACCESSORIES NOT INCLUDED

Accessories to be ordered separately.



AC146

SPIKE

Stainless steel ground spike.

Compatible for all products of the series.