




Vetra Sphera

Nava + Arosio



PRODUCT WEIGHT 0,70 kg



Vetra Sphera Small 600

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 640 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.

Code Example

902001 .27 .DF .07 .0

Accessories p. 399



902001
3W
Transparent Glass

| CCT | Beam Angle | lm | lm/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |




902002
3W
Opal Glass

| CCT | Beam Angle | lm | lm/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |

Remote Driver Selection

| Brand | Manufacturer code | Type | Watt | IP Rate | Number of fixtures |
|----------|-------------------|------------------------|------|---------|--------------------|
| Meanwell | LPV-20-24 | Contant voltage 24V DC | 20W | IP67 | min 1 - max 4 |
| Meanwell | LPV-35-24 | Contant voltage 24V DC | 35W | IP67 | min 1 - max 8 |



PRODUCT WEIGHT 0,90 kg



Vetra Sphera Small 900

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 940 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.

Code Example

902003 .27 .DF .07 .0

Accessories p. 399



902003
3W
Transparent Glass

| CCT | Beam Angle | lm | lm/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |



902004
3W
Opal Glass

| CCT | Beam Angle | lm | lm/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |


| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |

Remote Driver Selection

| Brand | Manufacturer code | Type | Watt | IP Rate | Number of fixtures |
|----------|-------------------|------------------------|------|---------|--------------------|
| Meanwell | LPV-20-24 | Contant voltage 24V DC | 20W | IP67 | min 1 - max 4 |
| Meanwell | LPV-35-24 | Contant voltage 24V DC | 35W | IP67 | min 1 - max 8 |




Obsidian Black



Wild Green



Dark Brown



PRODUCT WEIGHT 1,10 kg



Vetra Sphera Small 1200

Code Example

902005 .27 .DF .07 .0

Accessories p. 399

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 1240 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



902005
3W
Transparent Glass

| CCT | Beam Angle | Im | Im/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |



902006
3W
Opal Glass



| CCT | Beam Angle | Im | Im/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |

Remote Driver Selection

| Brand | Manufacturer code | Type | Watt | IP Rate | Number of fixtures |
|----------|-------------------|------------------------|------|---------|--------------------|
| Meanwell | LPV-20-24 | Contant voltage 24V DC | 20W | IP67 | min 1 - max 4 |
| Meanwell | LPV-35-24 | Contant voltage 24V DC | 35W | IP67 | min 1 - max 8 |





PRODUCT WEIGHT 0,80 kg



Vetra Sphera Big 600

Code Example

902007 .27 .DF .07 .0

Accessories p. 399

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 720 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



902007
3W
Transparent Glass

| CCT | Beam Angle | Im | Im/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |



902008
3W
Opal Glass



| CCT | Beam Angle | Im | Im/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |

Remote Driver Selection

| Brand | Manufacturer code | Type | Watt | IP Rate | Number of fixtures |
|----------|-------------------|------------------------|------|---------|--------------------|
| Meanwell | LPV-20-24 | Contant voltage 24V DC | 20W | IP67 | min 1 - max 4 |
| Meanwell | LPV-35-24 | Contant voltage 24V DC | 35W | IP67 | min 1 - max 8 |





PRODUCT WEIGHT 1,00 kg



Code Example

902009 .27 .DF .07 .0

Accessories p. 399

Vetra Sphera Big 900

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 1020 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



902009
3W
Transparent Glass

| CCT | Beam Angle | Im | Im/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |



902010
3W
Opal Glass



| CCT | Beam Angle | Im | Im/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |

Remote Driver Selection

| Brand | Manufacturer code | Type | Watt | IP Rate | Number of fixtures |
|----------|-------------------|------------------------|------|---------|--------------------|
| Meanwell | LPV-20-24 | Contant voltage 24V DC | 20W | IP67 | min 1 - max 4 |
| Meanwell | LPV-35-24 | Contant voltage 24V DC | 35W | IP67 | min 1 - max 8 |





PRODUCT WEIGHT 1,20 kg



Vetra Sphera Big 1200

Code Example

902011 .27 .DF .07 .0

Accessories p. 399

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 1320 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



902011
3W
Transparent Glass

| CCT | Beam Angle | Im | Im/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |



902012
3W
Opal Glass

| CCT | Beam Angle | Im | Im/w |
|------------|--------------|-----|-------|
| .27 2700°K | .DF diffused | 110 | 36.60 |
| .30 3000°K | .DF diffused | 120 | 40.00 |
| .40 4000°K | .DF diffused | 140 | 46.60 |

| Finish | Dimming |
|---------------------|-----------|
| .07 Obsidian Black | .0 ON/OFF |
| .08 Wild Green | |
| .09 Dark Brown | |

Remote Driver Selection

| Brand | Manufacturer code | Type | Watt | IP Rate | Number of fixtures |
|----------|-------------------|------------------------|------|---------|--------------------|
| Meanwell | LPV-20-24 | Contant voltage 24V DC | 20W | IP67 | min 1 - max 4 |
| Meanwell | LPV-35-24 | Contant voltage 24V DC | 35W | IP67 | min 1 - max 8 |

ACCESSORIES NOT INCLUDED

Accessories to be ordered separately.



AC146

SPIKE

Stainless steel ground spike.

Compatible for all products of the series.