





Vetra Filis

Nava + Arosio



PRODUCT WEIGHT 0,80 kg



Code Example

903001, .27, .DF, .07, 0

Accessories p. 402

Vetra Filis 600

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 720 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



903001
3W
Transparent Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	





903002
3W
Opal Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8



PRODUCT WEIGHT 1,00 kg



Vetra Filis 900

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 1020 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.

Code Example

903003, .27, .DF, .07, .0

Accessories p. 402



903003
3W
Transparent Glass

CCT	Beam Angle	Im	Im/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	




903004
3W
Opal Glass

CCT	Beam Angle	Im	Im/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8




Obsidian Black



Wild Green



Dark Brown



PRODUCT WEIGHT 1,20 kg



Vetra Filis 1200

Code Example

903005 .27 .DF .07 .0

Accessories p. 402

Outdoor lighting solution designed to guide and enhance exterior spaces with refined illumination. Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 1320 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.



903005
3W
Transparent Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	



903006
3W
Opal Glass

CCT	Beam Angle	lm	lm/w
.27 2700°K	.DF diffused	110	36.60
.30 3000°K	.DF diffused	120	40.00
.40 4000°K	.DF diffused	140	46.60

Finish	Dimming
.07 Obsidian Black	.0 ON/OFF
.08 Wild Green	
.09 Dark Brown	

Remote Driver Selection

Brand	Manufacturer code	Type	Watt	IP Rate	Number of fixtures
Meanwell	LPV-20-24	Contant voltage 24V DC	20W	IP67	min 1 - max 4
Meanwell	LPV-35-24	Contant voltage 24V DC	35W	IP67	min 1 - max 8

ACCESSORIES NOT INCLUDED

Accessories to be ordered separately.



AC146

SPIKE

Stainless steel ground spike.

Compatible for all products of the series.

